



SPECIFICATION

P/N: LCT-MD1002-01U

Preliminary

光圓科技股份有限公司

LED CIRCLE Technology Corporation


新竹市竹光路 8 號 14 樓之 8

14F-8, No. 8, Zhu-Guang Rd., HsinChu City, Taiwan

WEB: www.ledcircle.com E-Mail: zeno@ledcircle.com TEL: +886-3-540-2430



+



Description

The **LCT-MD1002-01U** is the **Alva-AH700-08** LED Driver, which is a Constant Current Output driver with universal AC input (85~264Vac) provides the 700mA constant DC current output, integrated with 1 or 2 or 3 or 4... ..or 10 pcs of compact LED Waterproof Module of **LC-MD1002-01**, which is composed by 3W Luxeon High Power LED, die-cast aluminum base, and precise focus lens. This modular product can be simple and compact light sources of LED luminaries or fixtures. With unique aluminum base, the heat is efficiently managed at preferable working temperature, thus enable LEDs having stable light output and lifetime. The LED is encapsulated in a unique structure to conform class IP65 protection. This unit offers easy and convenient design solutions to both lights manufacturer and lighting designer. *Other size, other LED, other colour pattern, and other array layout are available on request.* Other LED CCD Drivers from our Alva product series are available. Please just to visit the web of www.ledcircle.com or contact with zeno@ledcircle.com for the detail information.

Features

- IP65 Waterproof.
- Robust, 3W high power solid state lighting.
- Unique shape, ultra slim, hidden source.
- Good heat dissipation.
- Dynamic, vivid colors.
- Low voltage operation.
- The heat is efficiently managed at preferable working temperature.
- Small/Compact size.
- Easy for being retrofitted into existing traditional lighting fixture and indoor/outdoor lighting system.

Benefits

- Long lifetime, free of maintenance
- To offer easy and convenient design solutions
- Have flexible configurations including Warm white, White, Red, Green, Blue, Amber and RGBW mixed and other customized configuration
- Light weight
- Enhance the value of your products
- Provides flexibility to designers
- It is a hazard free product
- It can be integrated in to existing lighting system
- Facilitates new fixture design
- Facilitates low profile fixture design

Materials


- **LED** : High power high brightness Luxeon 3W.
- **Metal base** : Extrusion Aluminum.
- **Lens** : High Optical grade High transparency PMMA
- **Cover cap** : Polycarbonate.
- **Wire** : Teflon wire 24AWG.
- **Screw** : Stainless.



Typical Applications

- Architectural lighting
- Garden lighting
- In-ground lights.
- Floodlight.
- Cove lighting
- Cornice lighting
- Landscape lighting
- Under-Water lighting
- Vending machine lighting
- Wall sconces
- Under-cabinet lighting
- Projectors
- Decorative lights
- Pool/fountain lights

Driver wiring Diagram (Alva-AH700-08 LED Driver + LC-MD1002-01 3W LED Waterproof Module)



Selection Guide	
Part Number	Description
LCT-MD1002-01U-3WW-XXX	3W Warm White Waterproof Module
LCT-MD1002-01U-3W-XXX	3W White Waterproof Module
LCT-MD1002-01U-3R-XXX	3W Red Waterproof Module
LCT-MD1002-01U-3G-XXX	3W Green Waterproof Module
LCT-MD1002-01U-3B-XXX	3W Blue Waterproof Module
LCT-MD1002-01U-3A-XXX	3W Amber Waterproof Module
LCT-MD1002-01U-XX-XXX	3W Customized Waterproof Module

Note:

1. The XX is the project code of the customized products .
2. The XXX is the lens options as following:

S06	6° Acrylic lens with Smooth surface
R38	38° Acrylic lens with Rough/ball surface

Electrical characteristics		
Input		
Parameter	Min	Max
Input Voltage Range	85Vac	264Vac
Input Frequency	47Hz	63Hz
Input Current	N/A	N/A
Efficiency	Typical 80%-85%	


Note: The **Input Current** is depended on the LEDs that you have selected. (Contact our engineer for the detail)

Environmental Ratings		
Parameter	Min	Max
Operating Ambient Temperature	-20	60
Storage Ambient Temperature	-20	80



Drawing and Diagram :

#1: LC-MD1002-01 3W LED Waterproof Module



#2: Alva-AH700-08 LED Driver (120mm*20mm)



Important: Please contact our engineer to ensure installation and maintenance being properly executed to obtain maximum performance, efficiency and durability from the LED lighting product.

Disclaimer: While every care has been taken with the details on this specification sheet, we accept no responsibility for any inaccuracies and reserve the right to change these specifications without notice to always ensure that you are receiving a superior product.

光圓科技股份有限公司

LED CIRCLE Technology Corporation

新竹市竹光路8號14樓之8

14F-8, No. 8, Zhu-Guang Rd., HsinChu City, Taiwan

WEB: www.ledcircle.com E-Mail: zeno@ledcircle.com TEL: +886-3-540-2430