



E-mail: <u>philips@ledcircle.com</u>

Tel: +886-3-5679283

Fax: +886-3-5678764

SPECIFICATION





P/N: LCTS-40S6P2



光圓科技股份有限公司 新竹市金山六街 55 號 1 樓 (新竹第二辦公室) LED CIRCLE Technology Corporation

lF, No. 55, Jin-Shan 6^{fb.} St., Hsin-Chu City 300, Taiwan, R.O.C. (Hsin-Chu 2nd Office) TEL: +886-3-567-9283 Fax: +886-3-567-8764 Web : <u>www.ledcircle.com;</u> Email: <u>philips@ledcircle.com</u> 高品質的 LED 照明產品就在光圓科技============ LC provides high quality LED Lighting products



LED Circle Technology Corporation

Web: <u>www.ledcircle.com</u>

E-mail: philips@ledcircle.com


Tel: +886-3-5679283

Fax: +886-3-5678764





Examples: Diameter=90mm ; Height=35





Description

The LCTS-40S6P2 is a Talent LED Module for Solar System. It is integrated by 20W high power LEDs and ALVA CCD power supply. It is good for traditional lighting fitted into existing fixture. The size including LED PCB and CCD power supply, the LEDs, the colour pattern, the array layout and the CCD driver layout are opened for being customized to meet the requirement of the existing fixture.

Features

- The heat is efficiently managed at preferable working temperature.
- Easy for being retrofitted into existing traditional lighting fixture.
- The Driver is designed professionally for the Solar Power System.

Benefits

- Have flexible configurations including Warm white, White, Red, Green, Blue, Yellow and RGB mixed and other customized configuration.
- Enhance the value of your products
- Provides flexibility to designers
- Super High Power LEDs.
- It is a hazard free product
- It can be integrated into existing lighting system
- Facilitates new fixture design
- Facilitates low profile fixture design
- Optimisation of the usage of the system power.

Typical Applications

- Architectural lighting
- Indoor lighting
- Ceiling lighting

Selection Guide				
Part Number	Description			
LCTS-40S6P2-20WW	20W warm White/24Vdc Input			
LCTS-40S6P2-20SW	20W Sun White/24Vdc Input			
LCTS-40S6P2-20R	R 20W Red/24Vdc Input			
LCTS-40S6P2-20G	20W Green/24Vdc Input			
LCTS-40S6P2-20B	20W Blue/24Vdc Input			
LCTS-40S6P2-20Y	20W Yellow/24Vdc Input			
LCTS-40S6P2-20M	20W RGB/24Vdc Input			
LCTS-40S6P2-XXX	Customized			

Note: The XXX is the project code of the customized products.

Electrical characteristics						
Input						
Parameter	Min	Мах				
Input Voltage Range	24Vdc+5%	24Vdc-5%				
Input Current	-	-				
Efficiency	85%	95%				




LED Circle Technology Corporation

Web: <u>www.ledcircle.com</u>	E-mail: <u>philips@ledcircle.c</u>			<u>m</u> Tel: +886-3-5679283	Fax: +8	86-3-5678764
Environmental Ratings			Operating Ambient Temperature	-10	60	
Parameter	Min	Max		Storage Ambient Temperature	-20	80

Drawing and Diagram

1. Alva CCD LED Driver. 30mm (L) x 15mm(W) x 3mm(H)



2. LED Module.90mm(D) x 35mm(H)



Indoor Applications:

#1: External Solar Panels + Internal Driver (Driver is integrated into the light fixture)



Important: Please contact our engineer to ensure installation and maintenance being properly executed to obtain maximum performance, efficiency and durability from the LED lighting product.

Disclaimer: While every care has been taken with the details on this specification sheet, we accept no responsibility for any inaccuracies and reserve the right to change these specifications without notice to always ensure that you are receiving a superior product.

光圓科技股份有限公司 新竹市金山六街55號1樓(新竹第二辦公室) LED CIRCLE Technology Corporation

lF , № . 55 , Jin-Shan 6th St., H*s*in-Chu City 300 , Taiwan , R.O.C. (Hsin-Chu 2nd Office) TEL : +886-3-567-9283 Fax: +886-3-567-8764 Web : <u>www.ledcircle.com</u>; Email: <u>philips@ledcircle.com</u> 高品質的 LED 照明產品就在光圓科技========== LC provides high quality LED Lighting products